

# ERTAIN model

The ERTAIN System operator can be adapted to the needs of each installation. It is prepared for heavy traffic, both in large (supermarkets, hotels, airports, hospitals...) and in small and medium buildings (offices, chemist's, restaurants, points of sale in general...). Its most important features are its silent movement when opening and closing, dynamic stability and its quick and easy installation.

### SECURITY AND RELIABILITY

As is the case for its "big brother" (Global System), the ERTAIN System control panel features the very latest in electronic control and safety systems. The system is certified according to the most demanding safety regulations and standards, including EN 60335-2-103, 73/23/EC, 2004/18/EC and 2006/42/EC.


### EASY TO INSTALL AND MAINTAIN

The box cover and motor unit are separated in order to make installation easier, and, therefore, it can be assembled by a single person.


The three-wheeled carrier system has been designed so that the wheels can be interchanged, and, hence, it reduces the total cost and ensures the continual operation of the door as a spare wheel is always available.

### FEATURES AND ADVANTAGES

- Modular and versatile (it has the same motorisation profile box as the Global System model).
- Adaptable to all types of profiles up to a width of 50 mm.
- Quick installation of the operator in the motorisation profile box by means of a special nut system.
- Strong carriers composed of three nylon wheels running between rails, thus helping to prevent derailments.
- Motor power control system with automatic reverse for user safety.
- Battery-powered panic-breakout opening system in the event of power failure.
- The simplicity of the mechanism makes it easy to maintain.
- Can be connected to a PC for centralized door control or for programming.



Compact profile



Slimline profile

### TECHNICAL SPECIFICATIONS

	1450 OPERATOR	1850 OPERATOR	3200 OPERATOR
Free passage (1 leaf)	750 - 1150	950 - 1550	700 - 3000
Free passage (2 leaves)	1100 - 2300	1100 - 3000	1000 - 3000
Maximum weight per leaf (2 leaves)	80 + 80 kg	80 + 80 kg	80 + 80 kg
Maximum weight per leaf (1 leaf)	120 kg	120 kg	120 kg
Opening speed	0,4 m/s - 0,7 m/s	0,4 m/s - 0,7 m/s	0,4 m/s - 0,7 m/s
Closing speed	0,2 m/s - 0,5 m/s	0,2 m/s - 0,5 m/s	0,2 m/s - 0,5 m/s
Maximum leaf thickness	50 mm	50 mm	50 mm
Power supply	220 v (single phase)	220 v (single phase)	220 v (single phase)
Maximum consumption	100 w	100 w	100 w
Operator measurements	135 x 165	135 x 165	135 x 165

### DOOR FRAME TYPES AVAILABLE

PANIC-BREAKOUT	COMPACT	SLIMLINE	CLIP	CLAMP
----------------	---------	----------	------	-------





#### STANDARD SYSTEM

- 1 Motor profile
- 2 Geared motor
- 3 Electronic panel
- 4 Power supply and battery
- 5 Tensor subset
- 6 Toothed endless belt
- 7 Carriers
- 8 Roller tracks
- 9 Motorisation profile box

We open  
doors for you

